

SD45INT

SD45EXT



### BID SPECIFICATIONS

STANDARD

- \* SELF-CONTAINED, AIR-COOLED CONDENSING UNIT
- \* TEMPERED GLASS FRONT AND SIDES
- \* DIGITAL DIAGNOSTIC CONTROL SYSTEM
- \* STATIONARY/FIXED FRONT GLASS
- \* DECORATIVE FINISH FRONT AND SIDES PANELS
- \* STAINLESS STEEL INTERIOR AND EXTERIOR BACK
- \* REFRIGERATED DECK
- \* REAR PLEXIGLAS DOORS
- \* DISPLAY CASE(S) TO BE SHIPPED FULLY ASSEMBLED
- \* THE STANDARD LIMITED WARRANTY INCLUDES:  
5 YEAR COMPRESSOR; 1 YEAR PARTS; 90 DAYS LABOR
- \* DISPLAY CASE(S) TO BE LABORATORY CERTIFIED AS DESCRIBED

OPTIONAL

- \* CASTERS
- \* GRANITE WORK SURFACE (OPERATOR SIDE)
- \* REMOTE CONDENSING UNIT
- \* DECORATIVE SIDE PANELS

- \* SIDE & FRONT PANELS PAINTED IN A GLOSSY FINISH (CASE SHIP IN BUFF WHITE PRIMER)



STANDARD END PANEL



DECORATIVE END PANEL



### Sacher Deli Curved Refrigerated Cases Technical Specifications

Updated Model no.	Old Model No.	Factory Code	Case Height	*Case Length	Case Depth	Crated Weight (lb)	Line Voltage	Breaker Size	Amp Draw	Working Temp F	Comp. HP
SD45INT	C83S-45*INT	RVS 45C	50.75"	*A & B*	41.61"	1020	115/1/60	20amps	10	41	1/3 HP
SD45EXT	C83S-45*EXT	RVS 45A	50.75"	*A & B*	41.61"	844	115/1/60	20amps	10	41	1/3 HP




STANDARD END PANEL



DECORATIVE END PANEL


\*Case lengths are specified with standard end panels

**A - Customer Side**  
SD45EXT = 45.43"



**B - Server Side**  
SD45EXT = 19.21"

**A - Customer Side**  
SD45INT = 17.20"



**B - Server Side**  
SD45INT = 43.42"

### PLAN / TOP VIEWS OF CORNER CASES

#### LISTINGS:



#### ELECTRICAL CONNECTION:

Display cases are shipped with applicable junction box for hardwired installation  
Options exist for several NEMA configurations  
Plug and/or receptacle configurations are at the discretion of the electrical installer

#### NOTE:

Required ambient conditions: 75°F; 55% RH  
Drawing and Specifications are subject to change without notice

CLABO North America, LLC  
33300 Central Avenue  
Union City, CA 94587 USA  
PH 800.672.2784  
FAX 510.441.0401  
<http://www.otl-usa.com>